

DS-682H

Price Computing Hanging Scale



Clear customer-side display

- 1000 hours continuous use with the alkaline battery
- Large and clear figures in the display
- Up to 30 kg capacity
- Auto power-off function
- Low battery warning indicator
- Quick set up design
- Ac or battery operation according to your needs
- Backlight display mode*
- Euro function*

*Features vary by market

Fast, accurate and friendly service: outdoors and indoors.

Specifications

Capacity and scale interval:

Max 3/6kg	Max 6/15kg	Max 15/30kg	Max 15/30lb
e=1/2g	e=2/5g	e=5/10g	e=0.005/0.01lb

Display:	Weight: 5 digits Unit price: 5 digits Total price: 6 digits
Power source and power consumption:	AC100-120V, 220-240V, 50/60Hz (factory preset) 20mA 3W, Battery (6XD cell) 9V 12mA 0.1W
Operating humidity:	Max.85%RH (Non-condensing)
Dimensions:	Console unit: 264(W)X107(D)X243(H) mm 10.39(W)X4.21(D)X9.57(H) inches Unit height: 698mm/27.48 inches
Platter size:	φ260X35(H)mm φ10.24X1.38(H) inches
Net weight:	4.88kg/10.75lb(including battery)

DS-682 Series Model Variation



DS-682H (Bench type)

*Complies with OIML R-76 Class III.

*Specifications are subject to change without notice.

TERAOKA SEIKO CO.,LTD.

13 12 KUGAHARA 5 CHOME OHTA KU,
TOKYO 146-8580 JAPAN
TEL:+81-3-3752-2131 FAX:+81-3-3752-2801